



## LANDING GEAR STRUT FAIRING

FAIRINGS ARE INSTALLED ON THE 4 FORWARD LANDING GEAR STRUTS BECAUSE THEIR ALIGNMENT IS MOSTLY ACROSS THE WIND.


GLUE STYROFOAM BLOCK, 5/8 X 1, TO TUBE, APPLY .06" DIAM. CARBON ROD TRAILING EDGE, SAND TO FAIRING CONTOUR, FILL WITH LIGHT SPACKLE, SAND SMOOTH AND COVER WITH INSIGNIA CLOTH.



## LEFT WHEEL & LANDING GEAR STRUT ASSEMBLY SEEN FROM FORWARD



## LEFT LANDING GEAR SEEN FROM INBOARD, IN PLANE OF WHEEL, SIDE STRUT NOT SHOWN



BMX BICYCLE WHEEL, STINGRAY REAR WHEEL RIM (4 IN. WIDE), 3/8 IN. AXLE, 20 X 4-1/2 TIRE & TUBE, ACTUAL INFLATED DIAMETER IS ABOUT 21-5/8 IN., 4-1/8 IN. WIDE (EXAMPLE: KENDA ROAD HOG TIRE, 20 X 4-1/4 SUNLITE TUBE, & SEALANT SLIME)

# B4S9

## STINGRAY BMX LANDING GEAR

BLOOP 4  
ULTRALIGHT  
AIRPLANE

M. SANDLIN  
MARCH 15  
2017