


SECURE SHOULDER HARNESS WITH 4 OR 5 LACINGS OF CONTROL TYPE LINE, LENGTH AS REQUIRED. USE 1/8 QUICKLINK THROUGH TWISTED TANG FOR SHOULDER HARNESS ATTACHMENT, SEE B4EX

FOUR POINT ADJUSTABLE AUTOMOTIVE SEAT BELT, PUSH BUTTON RELEASE (EXAMPLE: "WESCO AUTOMOTIVE 4 POINT HARNESS SEAT BELT, PUSH BUTTON RELEASE, 2 INCH WIDTH"). STAMPED METAL END BRACKETS ARE REMOVED FROM BELT (3 PLACES) & REPLACED WITH STEEL QUICKLINKS AS SHOWN.



SEAT BELT ENDS ARE JOINED BY A 3/16" STEEL QUICKLINK

SIMPLIFIED VIEW OF REAR END OF NOSE SECTION MAIN FRAME, VIEWED FROM ABOVE

SIMPLIFIED VIEW OF SEAT & TOP FRAME OF NOSE SECTION, VIEWED FROM RIGHT SIDE

B4N12

**SEAT
BELTS**

BLOOP 4
ULTRALIGHT
AIRPLANE

M. SANDLIN
JULY 27
2016